## BANDIDO







1667203 • Amber Lens



- + ALL POLYCARBONATE FRAME WRAP-AROUND FIT
- + AMBER LENS AVAILABLE FOR BETTER CONTRAST AND PERCEPTION IN LOW LIGHT CONDITIONS
- **+** ASL ANTI-FOG / ANTI-SCRATCH COATING
- **+** SINGLE PIECE, OPTICALLY CORRECT, 10 BASE LENS



# BANDIDO

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
BANDIDO	Clear	1667201	Ю	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	Smoke	1667202	l3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	Amber	1667203	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

### LENS MARKING

- 1. The letter 'l' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear and amber lenses.

#### **OCULAR LENS CATEGORY:**

- O. Range of luminous transmittance 80-100% (clear & amber).
- 3. Range of luminous transmittance 8 -18% (smoke).

#### **APPLICATIONS**

- Assembly and production work
- Process work
- Emergency response
- Drilling
- Laboratory and dental
- Driving
- Solar UV exposure

## LENSES

- 2mm polycarbonate
- 10 base curve
- 'ALS' Anti-fog/anti-scratch coating on both sides of lens: Clear, Smoke and Amber
- 100% UV 385 Clear
- 100% UV 400 Amber and Smoke

## CLEANING AND STORAGE

**CLEANING:** Bollé Safety recommends only using our **Ø⊂LEAN** Lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40°, humidity <90%.

## MAIN MARKETS

- Manufacturing
- Petrochemical
- Construction
- Government
- Mining
- · Medical and dental
- Food Industry

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 10			
FRAME	PC			
STRAP	Non Applicable			
FOAM	Non Applicable			
SPARE LENSES	No			

## FRAME MARKING

**AS/NZS 1337.1.2010**: Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

#### ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd 32-40 Fairchild Street Heatherton VIC 3202 T: 1300 138 098 E: safety@bolle.com.au

#### **NEW ZEALAND:**

Bollé New Zealand Limited Unit 5, 114 Sawyers Arms Road Papanui, Christchurch 8052 T: 03 3751400 E: bolle@bolle.co.nz

