

LOWRIDER



Gloss Jet Black / Smoke Lens •
1651202



Gloss Jet Black / Grey Polarised
Lens • 1651207



27 g

- + RUBBER NOSE PADS AND TEMPLE TIPS FOR SUPERIOR COMFORT AND A NON-SLIP FIT**
- + GREY POLARIZED LENS, TRUE COLOUR DEFINITION WHILST FIGHTING HARSH GLARE**
- + 'ALS' ANTI-FOG/ANTI-SCRATCH COATING**

+ FIT: MEDIUM/LARGE

bollé
SAFETY

LOWRIDER

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
LOWRIDER	 Gloss Jet Black / Smoke Lens	1651202	IO & 	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum 
	 Gloss Jet Black / Grey Polarised Lens	1651207	I3 & 	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum 

LENS MARKING

 Platinum is a permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Emergency response
- Driving
- Solar UV exposure
- Rigging
- High glare, outdoor work places

MAIN MARKETS

- Manufacturing
- Transport
- Construction
- Local Government/ Councils
- Utilities
- Manufacturing

LENSES

- 2mm polycarbonate
- 8 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of the lens: Smoke only
- 100% UV400: Smoke, Polarised

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our  Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	No
FOAM	No
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz